

# **WORX RACING** **WORX COMPONENTS**

Pty Ltd A.C.N. 073 435 033

1/12 Ereton Drive Labrador Queensland Australia 4215

Phone: 61 7 5537 7181 Fax: 61 7 5537 7381

## **INSTALLATION INSTRUCTIONS**

**PART NUMBER: WR306                      WORX RIDE PLATE**  
**KAWASAKI 750      SXI PRO / SXR 800**

**IMPORTANT :**    READ ALL INSTRUCTIONS BEFORE PROCEEDING WITH INSTALLATION

Tools necessary for installation :                      1 x Tube of silicone

Parts Supplied :    1 x WORX Ride Plate  
   1 x 5mm Allen key

1. Roll Ski onto left side (refer to manufacturers instructions )  
Remove stock ride plate and wipe clean any old silicone from the hull and threaded inserts
2. Fill threaded inserts with silicone and apply a small amount of silicone to the mounting surfaces of your new Worx ride plate
3. Fit the Worx ride plate into position using the stock allen head bolts.
4. Wipe off excess silicone with a damp cloth. Allow 4-6 hours for the silicone to cure before riding
- 5 Regularly cheque that all bolts are tight

Thank you for purchasing **Worx Racing Components** products. We believe that **Worx Racing Components** products are among the finest watercraft parts available.

A great deal of time and effort has gone into the design and development of this product to ensure that it will perform to the highest standard and that installation will be a relatively straight forward procedure. If you have any comments on the performance/or installation of our parts, please contact us on the numbers listed on page one or through your local dealer.

**“DON'T SETTLE FOR SECOND BEST”**

**RIDE SAFLEY, PROTECT OUR ENVIROMENT**  
**AND RESPECT OTHERS WHO SHARE OUR WATERWAYS**

# **WORX RACING** **WORX COMPONENTS**

Pty Ltd A.C.N. 073 435 033

1/12 Ereton Drive Labrador Queensland Australia 4215

Phone: 61 7 5537 7181 Fax: 61 7 5537 7381

## **INSTALLATION INSTRUCTIONS**

**PART NUMBER: WR306                      WORX RIDE PLATE**  
**KAWASAKI 750      SXI PRO / SXR 800**

**IMPORTANT :**    READ ALL INSTRUCTIONS BEFORE PROCEEDING WITH INSTALLATION

Tools necessary for installation :                      1 x Tube of silicone

Parts Supplied :    1 x WORX Ride Plate  
   1 x 5mm Allen key

1. Roll Ski onto left side (refer to manufacturers instructions )  
Remove stock ride plate and wipe clean any old silicone from the hull and threaded inserts
2. Fill threaded inserts with silicone and apply a small amount of silicone to the mounting surfaces of your new Worx ride plate
3. Fit the Worx ride plate into position using the stock allen head bolts.
4. Wipe off excess silicone with a damp cloth. Allow 4-6 hours for the silicone to cure before riding
- 5 Regularly cheque that all bolts are tight

Thank you for purchasing **Worx Racing Components** products. We believe that **Worx Racing Components** products are among the finest watercraft parts available.

A great deal of time and effort has gone into the design and development of this product to ensure that it will perform to the highest standard and that installation will be a relatively straight forward procedure. If you have any comments on the performance/or installation of our parts, please contact us on the numbers listed on page one or through your local dealer.

**“DON'T SETTLE FOR SECOND BEST”**

**RIDE SAFLEY, PROTECT OUR ENVIROMENT**  
**AND RESPECT OTHERS WHO SHARE OUR WATERWAYS**